

# Fastener Data Sheet

## Sizes & Quantities:

#	Shank Length	Shank Gage	Fastening Range Max. Total Thickness	Required Deck Penetration	*Pieces/ Pound		
						Pieces/ Box*	Pounds/ Box
1	3/4"	9	-	3/4"	84	1,000	16
2	7/8"	9	-	7/8"	75	1,875	25
3	1"	9	-	1"	76	1,900	25
4	1 1/4"	9	1/4"	1"	70	1,750	25
5	1 1/2"	9	1/2"	1"	64	1,600	25
6	1 3/4"	9	3/4"	1"	59	1,475	25
7	2"	9	1"	1"	52	1,300	25
8	2 1/2"	9	1 1/2"	1"	40	1,000	25
9	3"	9	2"	1"	28	700	25
10	3 1/2"	9	2 1/2"	1"	16	400	25
11	4"	9	3"	1"	4	100	25



Patent Pending

### Uses:

- Base sheet fastener (deck or wall)
- Roof membrane fastener (deck or all)
- Base flashing fastener (wall)

## Design Options:

Shank Types	Tube Material	Container	Cap Diameter	Nail Materials
Smooth	Hardened Steel	25 lbs. Boxes	1"	Metal

## Design Features:

- Wider gauge shank to increase strength and hold
- Head and nail shank are welded together (an exclusive feature)
- The "original" capped roofing nail
- Installed with hand hammer
- Round head will not puncture roof membrane
- Fits perfectly in the 2" and 3" Simplex Rupture Discs
- Fast, Affordable, and Strong

## Notes:

Ideal for curtain walls and parapets

## Approvals:

American Plywood Association  
FFN-105b Type II, Style 27

## Rupture Discs:

Made of Galvalume metal to prevent corrosion  
Designed to fit all simplex nails  
Disc will increase rupture resistance to softer metals  
2" Rupture Disc is recommended for base sheet attachment  
3" Rupture Disc is recommended for insulation attachment.  
Ideal for curtain walls and parapets.

Disc Diameter	Disc Shape	Disc Design	*Pieces /Pound	*Pieces /Box	Pounds/ Box
2"	Round	Parabolic	50	1000	20
3"	Round	Parabolic	23	1000	45



**Simplex Nails, Inc.** 800-622-3354 Fax: 770-822-6822  
100 Petty Road, Suite A \* Lawrenceville, GA 30043 \* www.simplexnails.com



Made in the U.S.A.