

Fastener Data Sheet

Sizes & Quantities:

#	Shank Length	Shank Gage	Fastening Range Max. Total Thickness	Required Deck Penetration	*Pieces / Pound	Box	
						*Pieces /Box	Pounds /Box
1	1 3/4"	0.108"	1/4"	1 1/4"		1,000	

*Approximate Count



Design Options:

Shank Types	Tube Material	Container	Cap Diameters	Nail Materials
Smooth	Zinc	Boxes	2"	Metal

Design Features:

- Assembled design allows for quick and quality installation
- The original "Fish Hook" roofing nail
- Zinc tube and plate allow for effective rust resistance
- The monolithic form insures product performance from shipping through the life of the roof
- Use half the amount of fasteners compared to fasteners with 1" diameter metal cap fasteners in order to achieve similar rupture values with most materials
- Sharp chisel point to allow for smooth entry
- Hi-carbon steel nail provides additional pull out resistance
- Installed with hand hammer, pole hammer, or the Simplex Tube-Lok® fastening tool
- Round head will not puncture roof membrane
- The most affordable in its class

Uses:

- Base Sheet Fastener
- Roof Insulation Board Fastener
- Recovery Board Fastener
- Asphalt Shingle Fastener
- Aluminum Shingle Fastener
- Slate Shingle Fastener
- Tile Shingle Fastener
- Metal Batten, Flat, and Standing

Pullout Results:

Tube-Lok®	(lbs.)
Light Weight Concrete	120.2
Permadeck	140
Cementitious	115

Tested by Laws Engineering.
Test performed in compliance with Dade County Protocol PA 117(A)

Approvals:



Approved Class I-90 Pattern: 9x12x12 *
Approximate usage: 124 per square